



LEDBLRD-XXAC-NW • LEDBLOV-XXAC-NW

LED COMMERCIAL CEILING LIGHT

This range of wall and ceiling lights offers an attractive and cost effective source of light that is designed to be flush mounted to both walls and ceilings.


With these we can offer options on oval or round design, size, lumen output and with or with onboard light and motion sensor.

With a IP54 rating it is ideal for most areas including stairwells, corridors, bathrooms and under verandah areas.

The standard base colour is white, with a black option also available on special request.



DIMENSIONS



LEDBLOV-12AC-NW

LEDBLOV-18AC-NW

LEDBLRD-12AC-NW

LEDBLRD-18AC-NW

TECHNICAL SPECIFICATIONS

CAT. NO.	LEDBLOV-8AC-NW	LEDBLOV-12AC-NW	LEDBLRD-12AC-NW	LEDBLRD-18AC-NW
Input Voltage	220-240V AC			
Input Current	77mA	115mA	115mA	172mA
Power	8W	12W	12W	18W
Lumens	550lm	850lm	850lm	1400lm
Power Factor	≥0.5			
Colour Temperature	4000K (NW)			
Ra.	80			
Beam Angle	115°			
Sensor	Microwave sensor, adjustable			
IP Rating	IP54			
Isolation Class	Class II			









PRODUCT IMAGES




PHOTOMETRICS







SENSOR









20 Neilpark Drive East Tamaki Auckland. NEW ZEALAND **phone: 64 9 272 5619**

