



**ECO  
LIGHT**  
INDUSTRIAL LED

**LED  
INDUSTRIAL  
FLOOD  
LIGHTS**

**LEDFL11-40**

## 40W LED INDUSTRIAL FLOOD LIGHTS

The LEDFL11 floodlight range is the light of choice for most general purpose domestic and commercial applications.

Made from a powder coated aluminium housing, with a frosted toughened glass lens and stainless steel fasteners, the LEDFL11 is a robust LED Floodlight made to withstand tough environmental conditions. DC options offer flexibility for different applications. Alternative mounting options such as cable tray make for a fast effective installation.

Note: Red, Blue & Green light output available on special order

Marine Coating & non standard housing colours are also available on special order.

### FEATURES

LED Sources	40W
Input Voltage	AC (85~265V, 50-60Hz) DV 12V or DC24V
Power Supply Efficiency	>90%
Power Factor	>0.98
LED Lighting Efficiency	100lm/W
Colour Rendering Index	Ra>80
Colour Temperature	Cool White 5700K Warm White 3000K (indent only)
Ambient Temperature	-40°C to 55°C
IP Rating	IP65
Lifespan	>50,000 hours
Eco-friendly	No UV, IR, Lead or Mercury
Materials	LM06 equivalent Aluminium, high intensity toughened glass
Weight	3.3kg
Dimensions	262x185x163mm



CAT NO.	Lumens	Power	Supply Voltage	Current
LEDFL11-40AC	3600	40W	85 ~ 265V AC	0.18A*
LEDFL11-40ACBK**	3600	40W	85 ~ 265V AC	0.18A*
LEDFL11-40ACNSC***	3600	40W	85 ~ 265V AC	0.18A*

\* AC Current rating at 230V AC; DC Current at 24V DC

\*\* Black housing

\*\*\* Marine Coating

Note: DC & Polycarbonate options are available on special request

SDOC is available on our website



20 Neilpark Drive  
East Tamaki  
Auckland.  
NEW ZEALAND  
phone: 64 9 272 5619

  
www.ecolight.co.nz

**INSTALLED PRODUCT IMAGES**



**DIMENSIONS**



20 Neilpark Drive  
East Tamaki  
Auckland.  
NEW ZEALAND  
phone: 64 9 272 5619