



INDUSTRIAL SERIES



CONSTRUCTION

The industrial (IN) body is constructed using an automotive type ABS747 making it highly durable with a robust, solid construction. a trip hazard. The extension arms fitted either side of the body The IN Series has an IP 65 rating which means it can be used in wet weather conditions. The shock-absorbing rubber used on both the base and the lid seal gives extra protection to the light. The built-in cable storage compartment means you won't forget

the charging cables and there are no dangling cables to form with an easy push-pull handle mean that you can choose the right height for your own individual needs. This innovation allows this powerful industrial light to illuminate a very wide area and provides benefits for endless applications.











SPECIFICATIONS

MODEL	IN1600L DS	IN1600LB DS	IN3500LB SS	IN1000L
Net Weight (kg)	7.95	11.3	11.2	4.9
Gross Weight (kg)	9.05	12.6	12.5	5.9
Open Height (mm)	1150			670
Closed Height (mm)	582			450
Width (mm)	335			270
Depth (mm)	222			170
Charging Voltage	100-240V AC/12V DC			
Light Type LED	Double Sided		Single Sided	
Lumens (lm)	1600 (each side)		High: 3500 Low: 1750	1000
Battery Run Time (hrs) Approximately	Single Side: 16-18 Double Side: 8-10	Single Side: 28-30 Double Side: 16-18	High: 14-16 Low: 28-30	High: 10-12 Low: 22-24 Flash: 50+
Battery Charge Time (hrs) Approximately	7-8	10-12		7-8

DIMENSIONS









