

LED 210MM CUTOUT DOWNLIGHTS

This dimmable LED downlight range covers most lighting levels required for residential applications. They are extremely robust and reliable, coming with a dimmable leading or trailing edge driver, and are designed to provide minimal glare. Their compact design means they can be installed into the tightest of cavity spaces and thermal management ensures maximum light output for an extended period of time. The standard surround faceplate is white, black and silver are available on special order. Dali and 1-10V driver options are also available on special request.

TECHNICAL SPECIFICATIONS

Power Consumption	32W
Input Voltage/ Output Current	200-240 V AC, 50/60Hz
Fixture Lumens	2656lm (4000K) 2720lm (5000K)
LED Lighting Efficiency	85lm/W
Colour Temperature	(NW) Natural White 4000K (PW) Pure White 5000K
Colour Rendering (Ra)	>83
Power Factor	>0.95
IP Rating	IP44 front face, IP20 driver
Lifespan	35,000 hours
LED	SAMSUNG LM80, L70
Eco-friendly	ROHS
Materials	Oxidised Aluminium, High Quality PMMA
Driver	Dimmable – leading or trailing edge. Short circuit protection
Working Temperature	-20°C to 50°C
Dimensions	230mm Faceplate, 210mm Cutout
Faceplate Colour	White



FEATURES

- Reduce Energy Costs by up to 50%
- IC Rating – abutted & covered
- External PF constant current driver
- Only 20°C heat gain on heat sink
- 3-Year Limited Warranty

Product Codes	Description
LEDDL210-32NW-WHITE	32W, Natural White (4000K) - White faceplate
LEDDL210-32PW-WHITE	32W, Pure White (5000K) - White faceplate

* This rating is for downlights only, the driver is excluded. It is recommended the driver is positioned on the closest ceiling joist, in free air with good ventilation

PRODUCT IMAGES



DIMENSIONS

