



LEDUV1500-31CW-SEN

Developed for use in commercial, industrial and food hygiene areas amongst many applications.

The 5FT series replaces either single tube 5ft or double tube 4ft fluorescent fitting.

This model comes with internal motion sensor ensuring maximum potential power savings.

FEATURES

- IP65 Waterproof, Dustproof, Corrosion & Chemical Resistant.
- >50,000 hours lifespan
- 3900 lumen output
- Designed for easy 'like for like' retrofitting
- Motion sensor integral

TECHNICAL SPECIFICATIONS

Fixture/Part No.	LEDUV1500-31CW-SEN
Power Consumption	31W
Fixture Lumens	3900lm
LED Lighting Efficiency	125lm/W
Colour Temperature	PW: 5000K
Colour Rendering(Ra)	>80
IP Rating	IP65
Calculated L70 (B10)	>50,000 hours
LED Array	2835 SMD LED Chips
Impact Resistance	IK09
Ambient Temperature	-40°C to +50°C
Power Factor	0.95
Size (mm)	5FT =1574L x 140W x 90H x 1200mmLF
Input Voltage	220-240V AC, 50/60Hz
Material	Chemical, corrosion resistant polymer body & lens, S5 brackets & Aluminium LED gear tray
Warranty	5 years



- Food Grade Areas
- Industrial Applications
- Tunnels

.

- Public Transport
- Under Verandahs
- Warehousing
- Car park buildings

NOTES:

- Other Colour temperatures and wattages available upon request
- Through wire options available on request
- Suspension wire kit available as additional item
- SDoC available on website



