



HIGH PERFORMANCE LED POLE TOP LUMINAIRES



WINDAGE - 0.04m²

SPECIFICATION

- Strong high-pressure die-cast aluminium top and column mount finished full polyester (RAL9006)
- High impact UV stabilised polycarbonate cover rated IK10
- Integral high efficiency driver
- Extremely efficient and long system life up to 100,000 hours
- Fits 76mm columns as standard (60mm to special order)
- Fitted with 10m flying lead
- Photocell option
- Zero upward light
- Fitted with 4000K LEDs

RANGE

LED	SYMMETRIC DISTRIBUTION	ASYMMETRIC DISTRIBUTION	APPROX. kg
37W	JUN 19200L	JUN 19202L	9.4
78W	JUN 19201L	JUN 19203L	9.4
101W	JUN 19658L	JUN 19659L	9.4

CIRCUIT TYPE - L - non-dimming (LED)


OPTIONS

DESCRIPTION	SUFFIX	EXAMPLE
Photocell	PC	JUN 19200LPC

ACCESSORIES


DESCRIPTION	CAT. No.
Backlight reducing shield kit	JUN 19204
Column adaptor to fit on 101mm diameter column	POT 101-76

PHOTOMETRIC GUIDE



ASYMMETRIC DISTRIBUTION

Luminaire Lumen Output:
37W = 5380lm
78W = 10420lm
101W = 12970lm



SYMMETRIC DISTRIBUTION

Luminaire Lumen Output:
37W = 5725lm
78W = 11015lm
101W = 13560lm

LED CHARACTERISTICS

CRI	70+
COLOUR TEMPERATURE	4000K
RATED LIFE (HOURS)	100K - L80/B10
PROTECTION	LUX GUARD
DRIVER EFFICIENCY	93%
REPLACEABLE	YES
POWER FACTOR	>0.95

LL/CW 136.3

For LED characteristics explanation see www.thorlux.com.au/led-characteristics

Zero Upward Light

Help reduce light pollution and protect the night sky by selecting zero upward light luminaires

DIMENSIONS

