



REALTA MICRO



3W silver version



6W graphite version

LOW LIGHT LEVEL, WALL MOUNTED LUMINAIRES



SPECIFICATION

- Strong high-pressure die-cast LM2 aluminium body
- Graphite full polyester powder finish. Silver option
- SmartScan emergency version with wireless test status reporting
- One piece injection moulded UV stabilised polycarbonate cover
- Fitted with 4000K LEDs

LED CHARACTERISTICS

CRI	80
COLOUR TEMPERATURE	4000K
RATED LIFE (HOURS)	63K - L80/B10
PROTECTION	LUX GUARD
DRIVER EFFICIENCY	80%
REPLACEABLE	YES
POWER FACTOR	>0.5
LL/CW	78.6

For LED characteristics explanation see www.thorlux.com.au/led-characteristics



RANGE

LED	CAT. No.	APPROX. kg
3W	RL 13543L	1.3
6W	RL 16607L	1.5

CIRCUIT TYPE - L - non-dimming (LED)

SILVER OPTION - add suffix **SV3** e.g. **RL 13543LSV3** etc.

▲ Can be wired during installation for maintained or non-maintained operation

ACCESSORY

DESCRIPTION	CAT. No.	APPROX. kg
Wall mounting kit for 20mm conduit	RL 15419	0.4

SILVER OPTION - add suffix **SV3** e.g. **RL 15419SV3** etc.

DIMENSIONS

